

DESCRIPTION

The column speaker is a small and compact type designed for high efficiency, wide range especially high frequency result and high power input handling capability. With the supplied bracket, the speaker be mounted in many different application.

SPECIFICATIONS

Rated Input	10 W (Max 15 W)
Rated Impedance	100 V line: Hot 1 kΩ - black, Com - white
Sound Pressure Level	93 dB (1 W, 1 m)
Frequency Response	80 - 20,000 Hz
Dispersion Angle	Horizontal: 200° (1 kHz); 98° (4 kHz) Vertical: 110° (1 kHz); 26° (4 kHz)
Speaker Component	10 cm Cone-type x 2
Connection	Speaker cord (2-core cabtyre cord $\phi 6$ mm (0.24"), gray)
IP Code	IP44
Finish	Enclosure Case: Extrude Aluminum, black, paint Side Panel: Resin, black, paint Punched Net: Surface tread steel plate, black, paint
Dimensions	140 (W) X 315 (H) X 140 (D) mm (5.51" X 12.40" X 5.51")
Weight	2.2 kg (4.85 lb)
Accessory	Speaker Bracket $\times 1$, Wall Bracket $\times 1$, BH Screw M5x60 Fe Blk 3-SEMS $\times 1$

APPEARANCE

