



TKDN ZS-760B/W-AS

2-Way Weatherproof Loudspeaker System



Bringing you
high sound quality
under all weather conditions.

The horn speaker that fits all your need for **excellent speech** and **BGM clarity** in the open...

ZS-760B-AS / ZS-760W-AS

2-Way Weatherproof Loudspeaker System



- Highly intelligible: suited to voice alarm, public address and BGM application by 2-way speaker system.
- IP66 certified: All weather durability, be it water or dust. Ideal for any fully outdoor applications.
- Special paint coat prevents color degradation, ensuring long-lasting exterior condition.
- Rotary switch facilitates hassle-free impedance change.
- Various mounting brackets available as accessories allowing flexibility of mounting the speaker on a platform, in the ceiling, on the wall or on a pole.

APPLICATION EXAMPLES



Parking spaces



Railway stations



Amusement parks



Sports fields

SPECIFICATIONS

	ZS-760B-AS	ZS-760W-AS
Rated Input	60 W (high impedance)	
Rated Impedance	100V Line: 170 Ω (60W), 330 Ω (30W), 670 Ω (15W), 1.3kΩ (7.5W) 70V Line: 83 Ω (60 W), 170 Ω (30 W), 330 Ω (15 W), 670 Ω (7.5W)	
Sensitivity (1 W, 1 m)	100 dB	
Maximum SPL (60W, 1 m)	117 dB	
Frequency Response	100Hz - 20 kHz	
Crossover Frequency	2.5 kHz	
Directivity Angle	Horizontal: 90°; Vertical : 80°	
Speaker Component	Low Frequency: 16 cm (6") cone-type High Frequency: 2.5 cm (1") dome tweeter	
Dust/Water Protection	IP66	
Connection	Speaker cord (Hot: Black; Com: White)	
Finish	Enclosure: ABS, Black, Paint Coating Punched Net: Surface-treated Steel Plate, Black, Paint Coating Bracket: Stainless Steel, Black, Powder Coating	Enclosure: ABS, White, Paint Coating Punched Net: Surface-treated Steel Plate, White, Paint Coating Bracket: Stainless Steel, White, Powder Coating
Dimensions	388(W) x 310(H) x 367(D)mm	
Weight	7.4kg	



Like us on Facebook
facebook.com/Toa Indonesia

TOA
Smiles for the Public

website: toa.co.id
Specifications are subject to change without notice.