

PAGING MICROPHONE

ZM-660D

DESCRIPTION

Designed for paging calls and general announcements, the ZM-660D desk—top microphone comes with a large talk switch and a lock lever for easy and convenient operation. Its robust anti-vibration construction and balanced output render the microphone resistive to noise.

■ SPECIFICATIONS

Туре	Moving coil microphone
Polar Pattern	Unidirectional
Rated Impedance	600 Ω , Balanced
Rated Sensitivity	-58 dB (1 kHz, 0 dB=1 V/Pa)
Frequency Response	
Output	ø5.0 (ø0.2"), 4-conductor (2-shielded) cable (2.5 m (98.43")) with 5-pin DIN plug
Talk Switch	1-push-to-talk switch, 1-locking lever, Short-off type
Remote Control	500 mA or less at 30 V DC
Finish	Microphone head: Zinc plated steel wire, gray baked paint
	Main unit: ABS resin, gray
Dimensions	100 (W) × 215 (H) × 150 (D) mm (3.94" × 8.46" × 5.91")
Weight	440 g (0.97 lb) (cord excluded)

^{*} Do not keep the lock lever placed in the locked state (ON position) for a long period of time. Doing so may cause poor conductivity in the lever switch due to deterioration with age, resulting in unit malfunction.

